



Sang Mao

SERIES M-9005C

1" Single-Phase Motor Protectors



Specifications


Protects motors : 1/6 HP To 5 HP
 Operating temperature : 90°C~150°C
 Operating tolerance : $\pm 5^{\circ}\text{C}$
 Resume temperature tolerance : $\pm 12^{\circ}\text{C}$
 Trip time : 10 ± 5 seconds
 (Customization as per request)
 Input power : 110-120 VAC/220-240 VAC
 Contacts Type: Normally Close
 Reset type : Automatic or Manual reset
 Base type : Eared or Round
 Terminal type : Fast Clip、Plate、Hook、Stub

Approvals


UL approval : 1/4 - 3 HP , 110-120 / 220-240 VAC , 90 °C- 135°C. (File No.: E125871)

Circuit Connection

Low Voltage



High Voltage



Dimensional Drawings (1" Single-Phase Motor Protectors)

Eared Base Manual Reset		Eared Base Auto Reset	
Round Base Manual Reset		Round Base Auto Reset	

Terminal Type

Dimension in mm

Fast Clip	Plate	Hook	Stub

Type Code Structure

95

A

E

M

A

F

1

1

A

06

Item: M-9005

Type: **A** = 3/4" Single-Phase
B = 3/4" Three-phase
C = 1" Single-Phase
D = 1" Three-phase

Base: **E** = Eared **R** = Round

Reset: **M** = Manual Reset **A** = Auto Reset

Operation Temperature:

Automatic Reset	
Open ±5℃	Close ±12℃
A : 90℃	57℃
B : 105℃	61℃
C : 105℃	69℃
D : 105℃	78℃
E : 120℃	61℃
F : 120℃	69℃
G : 120℃	78℃
H : 120℃	92℃
I : 135℃	61℃
J : 135℃	69℃
K : 135℃	78℃
L : 135℃	92℃
M : 135℃	102℃
N : 150℃	78℃
O : 150℃	102℃
P : 150℃	115℃

Manual Reset	
Open ±5℃	Close ±12℃
S : 90℃	54℃
T : 105℃	63℃
U : 105℃	74℃
V : 120℃	74℃
W : 135℃	96℃
Y : 150℃	96℃
Remark: - 20℃ No Reset	

Terminal Type: **F** = 2 Fast Clip (for 3/4" & 1" Single-Phase)
G = 3 Fast Clip (for 3/4" & 1" Single-Phase)
P = 3 Plate **Q** = 6 Plate **S** = 2 Stub **T** = 3 Stub
H = 2 Hook **I** = 3 Hook **J** = 6 Hook

Electrical Ratings: **1** = 110-120 VAC **2** = 220-240 VAC **3** = 440-480 VAC
4 = 110-120 / 220-240 VAC **5** = 220-240 / 440-480 VAC

Ambient Temperature: **1** = 0° ~ 10° **2** = 11° ~ 20° **3** = 21° ~ 30° **4** = 31° ~ 40°
5 = 41° ~ 50° **6** = 51° ~ 60° **7** = 61° ~ 70° **8** = 71° ~ 80°
9 = OVER 81°

Full Load Current:

A : 1A	J : 10A	S : 19A	1 : 27-28A
B : 2A	K : 11A	T : 20A	2 : 29-30A
C : 3A	L : 12A	U : 21A	3 : 31-32A
D : 4A	M : 13A	V : 22A	4 : 33-34A
E : 5A	N : 14A	W : 23A	5 : 35-36A
F : 6A	O : 15A	X : 24A	6 : 37-38A
G : 7A	P : 16A	Y : 25A	7 : 39-40A
H : 8A	Q : 17A	Z : 26A	8 : 41-42A
I : 9A	R : 18A		9 : 43-44A

Lock Load Current (Customization as per request)