



Sensata  
Technologies

## 2AM/3AM/4AM/8AM Motor Protectors

**KLIXON®**

### Proven products backed by the leading innovators in protection technology.

Klixon® automatic motor protectors (AM series) are small, light weight and sensitive to temperature and current. The sealed steel cases will stand most dip and bake processes and can be mounted directly on motor windings for fast detection of temperature changes.

#### Operation

These on-winding motor protectors feature the Klixon® snapaction bimetallic disc in a normally closed circuit. The disc is actuated by the current passing thru it and the heat conducted from the motor windings. When the temperature reaches a predetermined calibration point corresponding to the maximum specified limit of the windings, the disc snaps open and interrupts the circuit. This permits maximum output while limiting the windings to a specified operating temperature. After the windings have cooled to the normal operating limit, the device resets automatically.

Closed Contacts



Open Contacts

#### 2AM/3AM/4AM wide application range

Available in a range of temperature and current sensitivities, the 2AM is suitable for a wide variety of applications. Designed to be mounted on the windings of electric motors and transformers, the 2AM protects against overheating and electrical overloading, offering the highest standards of safety and long term reliability.


#### Robust sealed construction


The 2AM's steel case is epoxy sealed and then insulated with a Mylar® sleeve allowing direct mounting on the windings. Robust construction and ability to withstand typical mechanical pressures make the 2AM ideal for installation during the manufacture of electric motors and transformers. Where necessary, additional sealing can be provided to prevent epoxy ingress with specialized impregnation processes.

#### Flexibility


By adding a customized 3rd lead, the standard device becomes a dual circuit 4AM, ideal protection for dual voltage or dual speed applications. For higher horse power applications, the 3AM provides protection for fault conditions up to 60 Amps. With a range of anticipating heaters matching protector to motor from 6 to 60 Amps and operating temperatures from 90 to 150°C, the 2AM series provides unsurpassed design flexibility for motor and transformer applications.

Mylar is registered trademark of Dupont




**2AM 7 B S H 0500 - 140**

**8AM 2 G V H A 10 - 120**


### 2AM Dimensions


NOTE: Nominal dimensions for reference purposes only (Millimeters)

### 8AM Dimensions



### Certifications

	115V 2AM 3AM 4AM	230V 50 60 50	UL standard 547 Guide No. 400-H13-C File E15962	CSA File LR23241C Guide No. 184-N-13.90 Class 3211		ENEC standard EN60730-2-2 File 2014531-19
8AM1	50					
8AM2	35					
8AM4	60		USR standard UL2111		CNR standard C22.2 No 77	standard EN60730-2-2 File 2014531-08



Sensata  
Technologies

## 8AM

Designed specifically for motors with a fast rate of temperature rise (25-35°C/sec), the 8AM provides economical protection for a full range of motors and transformers ranging from washing machines to vacuum cleaners; computer disk drives to high capacity automotive motors.

This unique design is capable of providing all mode protection:


- Locked rotor
- Running overload
- Low voltage
- Run both winding

### Here's why you should be using the 8AM protector in your product:

- Compact, easy to install
- Individually temperature calibrated and checked
- Positive make-and-break with Klixon® snapaction disc
- Gasketed steel case suitable for many impregnation processes
- Current and temperature sensitivity for maximum design flexibility
- Specially designed terminals for easy addition of wireleads.

### Typical applications:

- Split-phase motors
- Capacitor start motors
- Ballast protection
- Transformers
- Automotive motors
- Solenoids



---

### TECHNICAL / SALES SUPPORT

Holland

Phone +31 546 879560 Fax +31 546 879204

Internet: [www.sensata.com](http://www.sensata.com)

Email: [info-cpe@list.sensata.com](mailto:info-cpe@list.sensata.com)

Important Notice: The products and services of Sensata Technologies and its subsidiaries described herein are sold subject to Sensata's standard terms and conditions of sale. Customers are advised to obtain the most current and complete information about Sensata products and services before placing orders. Sensata assumes no liability for applications assistance, customer's applications or product designs, software performance, or infringement of patents. The publication of information regarding any other company's products or services does not constitute Sensata's approval, warranty or endorsement thereof.

Printed in Holland, June 2010

Sensata  
Technologies